

# PrecisionID Code 128 Barcode Fonts User Manual



**Updated 2018**

© Copyright 2018 PrecisionID.com | All Rights Reserved | [Legal Notices](#)

PrecisionID Code 128 Barcode Font Product Overview .....	2
System Locale, Language and Codepage Support .....	2
Installation .....	2
Microsoft Windows .....	2
Mac .....	2
Other Operating Systems .....	2
Font Encoders and Application Tutorials .....	2
Examples .....	3
Crystal Reports .....	3
Microsoft Excel .....	4
Microsoft Word Mail Merge .....	6
Specific Implementations .....	7
Creating Check Digits in Other Applications .....	7
Printing Text Below the Barcode .....	7
GS1-128 Barcodes .....	7
Specifications .....	8
Font Point Sizes and X Dimension (Narrow Bar Width) .....	8
Font Names and Bar Code Height .....	8
Code 128 Character Sets A, B, and C .....	9
The Code 128 Character Chart .....	10

**Notice:** When you use this product you agree to the End User License Agreement (EULA). The EULA is provided as a file in the package for this product. To view the license online, please visit <http://www.precisionid.com/licenses/>

**Limitations of the demo version:** The demo version of this product may be used for evaluation purposes only. In the demo version, the number 7 and the characters G, S and X contain the demo watermark. All other characters and symbols are exactly the same as the purchased version. If you are using the demo version and you would like to order, please visit: <http://www.precisionid.com/>

# PrecisionID Code 128 Barcode Font Product Overview

[Code 128 Barcode Fonts](#) are more complex most other linear barcodes because they require a check digit and contain 3 character sets with special switch functions. PrecisionID supplies several Font Encoders, that will format data to the font, calculate any check digits that are required, and provide easy application integration. Refer to the Examples folder of the product zip file and the [Font Encoders](#) section of the website for a complete selection. This package also provides working examples for Word, Access, Excel and Crystal Reports as examples.

## System Locale, Language and Codepage Support

To represent all of the Code 128 characters in the specification, some characters must be placed at locations that are different in other languages. Therefore, to ensure correct formatting, the system regional setting should be set to English USA or one of the following codepages: 1252 Latin-1, 1250 European, 1251 Cyrillic, 1253 Greek, 1254 Turkish or 1256 Arabic. To view the System Locale settings in Windows: Click Start, then Control Panel, Click Clock, Language and Region, Click Region, The Region and Language options dialog appears. Click the Administrative or Advanced tab, (If there is no Advanced tab, then you are not logged in with administrative privileges.) In the Language for non-Unicode programs section, click Change system locale and select the desired language. Click OK and Restart the computer to apply the change.

## Installation

### Microsoft Windows

PrecisionID recommends using the supplied **exe** file to install the fonts automatically in Windows. If you wish to manually install the fonts in Windows, open the Control Panel and choose Fonts; then choose Install New Font and browse to the folder that contains the code 128 bar code fonts with the TTF extension extracted from the zip file.

### Mac

PrecisionID fonts are compatible with all versions of Macintosh OS Version 10.1 and greater (OSX). Drag the barcode font files with the TTF extension to the Library/Fonts folder of your hard drive. To activate the fonts, restart the application; some applications may require a restart of the computer.

### Other Operating Systems

We supply Windows TrueType (TTF) fonts as well as Binary (PFB) and ASCII (PFA) versions of PostScript fonts. Consult the documentation for your operating system about instructions and which barcode font to install.

## Font Encoders and Application Tutorials

PrecisionID supplies several Font Encoders, that will format data to the font, calculate any check digits that are required, and provide easy application integration. Refer to the Examples folder of the product zip file and the [Font Encoders](#) section of the website for a complete selection. To calculate the check digit manually, we suggest following the Visual Basic source code provided. This code is located in the [Examples\VB Module](#) folder of the package.

## Examples


The following tutorials are saved in the examples folder of the product zip file. Refer to the examples provided in this folder for quick and accurate implementation.

### Crystal Reports

This example was created in Crystal Reports version 9. Implementation in other versions of Crystal Reports are very similar if not identical.

1. **Copy the formula object to the clipboard.**

Extract and open the “Crystal Reports Font Formulas.rpt” file that is in the \examples\ folder of the product zip file. Right-click on the font formula that is needed and choose Copy.



2. **Paste the object into your report.**

Open your Crystal Report and switch to design mode. Choose Edit – Paste or CTRL-V where the object is needed and size it appropriately to contain the entire symbol.



3. **Change the data source in the formula of the object.**

Right-click on the object and choose Edit – Formula. Modify DataToEncode= to connect to the data source; for example: DataToEncode = ({Table.Field})

If an error such as "A string is required" appears, the data will need to be converted to a string with a VB crystal function such as ToText or cStr.


For example: DataToEncode = ToText( {Table.Field})

4. The barcode should now be visible when you run the report.




## Microsoft Excel


1. NOTE: the [PrecisionID C128 T04](#) font is formatted specifically for use in Microsoft Excel. Other fonts may work but may not format properly in the cells.
2. In this example we will create a barcode in cell **B8** using the data from cell **A8** for the barcode.
3. Extract the [PrecisionID\\_C128\\_Module.bas](#) file from the package and place it in a folder of your choice.
4. Before creating Code 128 barcodes in Excel , you must enable the Developer Menu to import the required module so it will run. In Excel , click the Office Button and select Excel Options at the bottom.




5. In the Popular Options check the “Show Developer Tab in the Ribbon”. Click OK.



6. Select the Developer Tab and click the Visual Basic Icon.



7. Choose File – Import File and navigate to the [PrecisionID\\_C128\\_Module.bas](#) file located in the [Program Files\PrecisionID Code 128 Font Package](#) folder. After this module is imported, it will be visible in the list of modules. Choose File – Close and return to Excel.




8. In cell B8, enter the formula `=PrecisionID_C128AUTO(A8)` which is required to format the data to the font.

	A	B
8	TEST 1234	=PrecisionID_C128AUTO(A8)

9. Notice that the formula changed the data from cell A8 and appended additional characters at the beginning and ending of the text. Also notice that numbers from the data are compressed into other characters; this is normal when using Code 128 Auto and the barcode contains 4 or more consecutive number characters.

	A	B
8	TEST 1234	ïTESTÂÇ,BÇï

10. With cell B8 selected, choose the **PrecisionID C128 T04** font, which is specifically formatted for use in Microsoft Excel, and choose 12 for the point size. PrecisionID also recommends centering the text in this cell so the barcode will contain white space before and after the barcode. It is required to select the appropriate barcode font for the formula being used. For example, a code 128 barcode formula requires a Code 128 barcode font.




11. After selecting the bar code font, the barcode will appear. Size the width of the column so that there is some white space before and after the bars of the barcode.

	A	B
8	TEST 1234	


12. To create an entire column of barcodes, choose Edit – Copy with cell B8 selected.
13. Highlight cells you wish to add barcodes to in column B and choose Edit - Paste. The formula will automatically adjust for the other cells.

## Microsoft Word Mail Merge


1. Open the mail merge document.
2. To create a barcode in a Word mail merge, insert a merge field from a data source that has already formatted the text for the barcode font. In this example, Excel is used as the data source. The Excel spreadsheet data source must already be setup with barcodes just like the Excel Tutorial in this document.
3. Select the Mailings menu item, click Start Mail Merge and select the type of document to create.




4. Click Select Recipients and select Use Existing List. Navigate to the spreadsheet with the barcode data. Finally select the Worksheet within the Workbook with the data, i.e. "sheet1".



5. Place the cursor at the location for the barcode and click Insert Merge Field and select the information to be inserted; i.e. "FormattedText".



6. If you click "Preview Results", the text formatted for the barcode from the data source appears.



Text formatted to barcode font:  
İTESTÂÇ.BÇİ

7. Select the text in the merged data and choose the **PrecisionID C128 08** font. Make the font 12 points in size.



8. For additional help, see Word Help or use the Mail Merge Wizard under Mailings - Start Mail Merge.

## Specific Implementations

### Creating Check Digits in Other Applications

The easiest method of creating source code for a check digit in a custom application is to use our [PrecisionID\\_C128\\_Module.bas](#) module as a guide. The module was written to be compatible with Visual Basic 6 and Microsoft Office VBA and may be viewed with a text editor. This module is located in the [Examples\VB Module](#) folder of the package.

### Printing Text Below the Barcode

Human-readable or text fonts are not provided in this package because they do not work well with Code 128. If you need to place text below the barcode, we suggest simply printing the data you are encoding in a text font below the barcode on your report.

### GS1-128 Barcodes

PrecisionID Font Encoders allow the creation of GS1-128 barcodes by simply substituting the ASCII 202 character for the FNC1 when in C128AUTO. For example, to create the GS1 barcode of (01)12345678901231(15)991231 the text of Ê011234567890123115991231 would need to be encoded where Ê is the ASCII 202 character or Chr(202) in VB. The text portion for this barcode type must be created as a separate field below the barcode using a text font. Variable AIs should be encoded last in the symbol and additional FNC1 characters must be encoded between two or more variable length AIs. Refer to [GS1](#) for additional information.



## Specifications

### Font Point Sizes and X Dimension (Narrow Bar Width)

Our fonts are designed to print with precision on high resolution printers as well as low resolution printers such as 203 dpi thermal barcode printers. When printing at 203 dpi, the point size chosen should be a multiple of 6. When printing at 300 dpi, the point size chosen should be a multiple of 4.

Font point size	X Dimension (narrow bar width) measured in mils (1/1000 of an inch)
6	5
8	7
12 (recommended)	10
16	13
20	16
24	20
36	30

### Font Names and Bar Code Height

The numbers at the end of the font name are to identify the height of the font in millimeters (mm) when printed at 12 points.

Font Name	Approximate Font Height at 12 points
PrecisionID C128 04	.18" or 04mm (use in Excel)
PrecisionID C128 08	.30" or 08mm
PrecisionID C128 12	.45" or 12mm
PrecisionID C128 14	.56" or 14mm (use for GS1-128)
PrecisionID C128 18	.70" or 18mm
PrecisionID C128 22	.90" or 22mm

## Code 128 Character Sets A, B, and C

The `PrecisionID_C128Auto(data)` function automatically switches between character sets to create the most compact barcode possible for the data. Most of the time the barcode will start with character set B as it has the broadest and most common variety of characters. When several consecutive numbers appear in the data, the function will switch to character set C and if a control character is encountered (such as a TAB or CR), the function will switch to character set A.

Some implementations of Code 128 may require the barcode be limited to a specific character set. If this is required, additional functions are provided that do not auto-switch. Refer to the Code 128 Character Chart for the specific characters available within each character set.

Character Set A	<code>PrecisionID_C128_A(<i>data</i>)</code>
Character Set B	<code>PrecisionID_C128_B(<i>data</i>)</code>
Character Set C	<code>PrecisionID_C128_C(<i>data</i>)</code>

# The Code 128 Character Chart

The fonts were created according to the chart below. If you have an advanced knowledge of the Code 128 specifications, you can use this chart to manually create your barcodes and calculate the check digit.

Value	Set_A	Set_B	Set_C	ASCII	Text
0	Space	Space	0	194	Å
1	!	!	1	33	!
2	"	"	2	34	"
3	#	#	3	35	#
4	\$	\$	4	36	\$
5	%	%	5	37	%
6	&	&	6	38	&
7	'	'	7	39	'
8	(	(	8	40	(
9	)	)	9	41	)
10	*	*	10	42	*
11	+	+	11	43	+
12	,	,	12	44	,
13	-	-	13	45	-
14	.	.	14	46	.
15	/	/	15	47	/
16	0	0	16	48	0
17	1	1	17	49	1
18	2	2	18	50	2
19	3	3	19	51	3
20	4	4	20	52	4
21	5	5	21	53	5
22	6	6	22	54	6
23	7	7	23	55	7
24	8	8	24	56	8
25	9	9	25	57	9
26	:	:	26	58	:
27	;	;	27	59	;
28	<	<	28	60	<
29	=	=	29	61	=
30	>	>	30	62	>
31	?	?	31	63	?
32	@	@	32	64	@
33	A	A	33	65	A
34	B	B	34	66	B
35	C	C	35	67	C
36	D	D	36	68	D
37	E	E	37	69	E
38	F	F	38	70	F
39	G	G	39	71	G
40	H	H	40	72	H
41	I	I	41	73	I
42	J	J	42	74	J

Value	Set_A	Set_B	Set_C	ASCII	Text
54	V	V	54	86	V
55	W	W	55	87	W
56	X	X	56	88	X
57	Y	Y	57	89	Y
58	Z	Z	58	90	Z
59	[	[	59	91	[
60	\	\	60	92	\
61	]	]	61	93	]
62	^	^	62	94	^
63	_	_	63	95	_
64	nul	`	64	96	`
65	soh	a	65	97	a
66	stx	b	66	98	b
67	etx	c	67	99	c
68	eot	d	68	100	d
69	eno	e	69	101	e
70	ack	f	70	102	f
71	bel	g	71	103	g
72	bs	h	72	104	h
73	ht	i	73	105	i
74	lf	j	74	106	j
75	vt	k	75	107	k
76	ff	l	76	108	l
77	cr	m	77	109	m
78	s0	n	78	110	n
79	s1	o	79	111	o
80	dle	p	80	112	p
81	dc1	q	81	113	q
82	dc2	r	82	114	r
83	dc3	s	83	115	s
84	dc4	t	84	116	t
85	nak	u	85	117	u
86	syn	v	86	118	v
87	etb	w	87	119	w
88	can	x	88	120	x
89	em	y	89	121	y
90	sub	z	90	122	z
91	esc	{	91	123	{
92	fs		92	124	
93	gs	}	93	125	}
94	rs	~	94	126	~
95	us	del	95	195	Ã
96	Fn 3	Fn 3	96	196	Ä

43	K	K	43	75	K
44	L	L	44	76	L
45	M	M	45	77	M
46	N	N	46	78	N
47	O	O	47	79	O
48	P	P	48	80	P
49	Q	Q	49	81	Q
50	R	R	50	82	R
51	S	S	51	83	S
52	T	T	52	84	T
53	U	U	53	85	U

97	Fn 2	Fn 2	97	197	Å
98	Shift	Shift	98	198	Æ
99	code C	code C	99	199	Ç
100	code B	Fn 4	code B	200	È
101	Fn 4	code A	code A	201	É
102	Fn 1	Fn 1	Fn 1	202	Ê
103	Start A	Start A	Start A	203	Ë
104	Start B	Start B	Start B	204	Ì
105	Start C	Start C	Start C	205	Í
	Stop	Stop	Stop	206	Î